CS161 Fall 2026 — Introduction to Computer Security — Exam Prep 10

Q1 *Memory Safety: EvanBond, Double-O \x90* **(19 points)**

Consider the following vulnerable C code:

```
1  void q(int spectre) {
2      char goldfinger[8];
3      fread(goldfinger, 13, 1, stdin);
4      for (int i = 0; i < 8; i++) {
5          goldfinger[i] = 0x90;
6      }
7  }
8
9  void m() {
10     q(007);
11 }
```

Stack at Line 2

RIP of `m`
(1)
(2)
(3)
SFP of `q`
(4)

Assumptions:

- All memory safety defenses are disabled.
- You run GDB and break before executing line 3. You find that the RIP of `q` has the value `0xffffd6c0`.
- You also find that `goldfinger` is located at address `0xffffd620`.
- Recall that the byte `0x90` is also known as the NOP (no-operation) instruction.
- Your goal is to execute the 4-byte-long SHELLCODE.

Q1.1 (2 points) What values go in blanks (1) through (4) in the stack diagram above?

- ◯ (1) SFP of `m` (2) RIP of `q` (3) `spectre` (4) `goldfinger`
- ◯ (1) SFP of `m` (2) `spectre` (3) RIP of `q` (4) `goldfinger`
- ◯ (1) RIP of `q` (2) `spectre` (3) SFP of `m` (4) `goldfinger`
- ◯ (1) RIP of `q` (2) `goldfinger` (3) `spectre` (4) SFP of `m`

Q1.2 (4 points) Which of these values does the exploit have to overwrite to execute `SHELLCODE`? Select all that apply.

- ☐ `goldfinger`
- ☐ SFP of `m`
- ☐ Least significant byte of the RIP of `q`
- ☐ `spectre`
- ☐ SFP of `q`
- ◯ None of the above

This content is protected and may not be shared, uploaded, or distributed.

Q1.3 (4 points) Provide an input to the `fread` on Line 3.

If a part of the input can be any non-zero value, use `'A' * n` to represent `n` bytes of garbage.

Q1.4 (2 points) Which memory safety defenses would cause the correct exploit from Q7.3 (without modifications) to fail? Consider each choice independently.

- ☐ Stack canaries
- ☐ Non-executable pages
- ◯ None of the above

Q1.5 (3 points) Which **values** of the RIP of `q` would cause the correct exploit from Q7.3 (without modifications) to fail? Select all that apply.

- ☐ `0xffffd640`
- ☐ `0xffffd630`
- ☐ `0xffffd620`
- ☐ `0xffffd610`
- ☐ `0xffffd600`
- ☐ `0xffffdbe0`
- ☐ `0xffffdbd0`
- ☐ `0xffffdbc0`
- ◯ None of the above

Q1.6 (4 points) When does the correct exploit from Q7.3 start executing instructions in `SHELLCODE`?

- ◯ When the function `fread` on line 3 returns
- ◯ When the `for` loop on line 4 completes
- ◯ When the function `q` on line 1 returns
- ◯ When the function `m` on line 8 returns

This content is protected and may not be shared, uploaded, or distributed.

Q2 *Memory Safety: Are you being fr ?* **(17 points)**

Consider the following vulnerable C code:

```
1  void foo(void) {
2      char msg[8];
3      fgets(msg, 8, stdin);
4      printf(msg);
5      fread(msg, 20, 1, stdin);
6  }
7
8  void vulnerable() {
9      int i;
10     char buf[20];
11     char cpy[20];
12     fread(buf, 20, 1, stdin);
13     for(i = 19; i >= 0; i--) {
14         cpy[i] = buf[19-i];
15     }
16     foo();
17 }
```

Stack at Line 2

RIP of `vulnerable`
(1)
(2)
`i`
(3)
`cpy`
(4)
(5)
(6)
`msg`

Assumptions:

- Stack canaries and non-executable pages are enabled, and all other memory safety defenses are disabled.
- You run GDB once and find that the library function `system` is located at the address `0xdeadbeef`.
- The RIP of `foo` is located at `0xffffdc90`. The RIP of `vulnerable` is located at `0xffffdcc8`.
- Your goal is to execute `system` with the 8-character string `"rm -rf /"` as the argument.

Q2.1 (1 point) What values go in blanks (1) through (3) in the stack diagram above?

- ◯ (1) canary (2) RIP of `foo` (3) SFP of `vulnerable`
- ◯ (1) canary (2) SFP of `vulnerable` (3) `buf`
- ◯ (1) SFP of `vulnerable` (2) canary (3) `buf`
- ◯ (1) SFP of `vulnerable` (2) `cpy` (3) canary

Q2.2 (1 point) What values go in blanks (4) through (6) in the stack diagram above?

- ◯ (4) canary (5) RIP of `foo` (6) SFP of `foo`
- ◯ (4) canary (5) SFP of `foo` (6) RIP of `foo`
- ◯ (4) RIP of `foo` (5) SFP of `foo` (6) canary
- ◯ (4) RIP of `foo` (5) `&msg` (6) SFP of `foo`

This content is protected and may not be shared, uploaded, or distributed.

Q2.3 (2 points) What type of vulnerability is present in this code? Select all that apply.

- ☐ Format string vulnerability
- ☐ Off-by-one
- ☐ ret2ret
- ☐ Buffer overflow
- ☐ Signed/unsigned
- ◯ None of the above

Q2.4 (3 points) Which of these inputs to `fgets` on Line 3 will always leak the value of the stack canary in the `foo` stack frame? Select all that apply.

Note: You are able to convert any numerical representation of the canary into a usable form.
Note: Stack canaries are four random bytes (no null byte).

- ☐ `'%x' * 3`
- ☐ `2 * '%c' + '%p'`
- ☐ `'%n' * 3`
- ☐ `'\xc0\xdc\xff\xff' + '%s'`
- ☐ `'\x88\xdc\xff\xff' + '%s'`
- ◯ None of the above

In the next two subparts, provide inputs that would cause the program to execute `system("rm -rf /")`. You may use `CANARY` to refer to the correct value of the stack canary, as leaked by `printf`.

Q2.5 (5 points) Input to `fread` at Line 12:

```
'A'*[          ] + '\x00' + '[                              ]' +
'[                                        ]' + 'A'*[          ]
```

Q2.6 (5 points) Input to `fread` at Line 5:

```
[                                                            ]
```

Q3 *Cryptogrpahpy: Obliviously Garbage* (11 points)

Alice has two messages: m_0 and m_1. Bob wants to retrieve one of the two messages, without Alice finding out which message Bob chose to retrieve.

To do this, Alice and Bob follow the *blind retrival* protocol below:

Setup:

1. Alice generates an RSA key pair: public key (N, e) and private key d. Alice sends (N, e) to Bob.
2. Alice generates two random values r_0 and r_1 and sends them to Bob.
3. If Bob chooses m_0, he will define $r_b = r_0$. Otherwise, he will define $r_b = r_1$.

Protocol Steps:

4. Bob generates a random value k.
5. Bob computes $v \equiv r_b + k^e \bmod N$ and sends this value v to Alice.

This content is protected and may not be shared, uploaded, or distributed.

6. Alice computes $k_0 \equiv$ _____ [Q3.1] and $k_1 \equiv$ _____ [Q3.2].

7. Alice sends $m_0' \equiv m_0 + k_0 \bmod N$ and $m_1' \equiv m_1 + k_1 \bmod N$ to Bob.

8. Bob recovers his desired message by computing $m_b \equiv$ _____ [Q3.3].

Q3.1 (1 point) Provide the value for k_0 in step 6.

- ◯ $k_0 \equiv (v + r_0)^d \bmod N$
- ◯ $k_0 \equiv (v \cdot r_0)^d \bmod N$
- ◯ $k_0 \equiv (v - r_0)^d \bmod N$
- ◯ $k_0 \equiv v^d - r_0 \bmod N$

Q3.2 (1 point) Provide the value for k_1 in step 6.

- ◯ $k_1 \equiv (v + r_1)^d \bmod N$
- ◯ $k_1 \equiv (v \cdot r_1)^d \bmod N$
- ◯ $k_1 \equiv (v - r_1)^d \bmod N$
- ◯ $k_1 \equiv v^d - r_1 \bmod N$

Q3.3 (1 point) Provide the value for m_b in step 8.

- ◯ $m_b \equiv m_b{}' + k \bmod N$
- ◯ $m_b \equiv m_b{}' \oplus k$
- ◯ $m_b \equiv m_b{}' - k \bmod N$
- ◯ $m_b \equiv m_b{}' \cdot k^{-1} \bmod N$

Q3.4 (1 point) Why can Alice not determine which message Bob chose to retrieve? Select the best answer.

- ◯ Because the value $v = r_b + k^e \bmod N$ is masked by the term k^e.
- ◯ Because r_0, r_1 are both randomly generated and therefore evenly distributed mod N.
- ◯ Because Bob's private RSA exponent d remains secret.
- ◯ Because Bob sends v over an encrypted channel, so Alice cannot read it directly.

This content is protected and may not be shared, uploaded, or distributed.

Subparts Q3.5 to Q3.8 are independent of earlier subparts.

Consider this protocol:

- Alice and Bob each have a secret bit (Alice has a, Bob has b).
- They want to compute the bitwise AND of their secret bits, such that both parties learn $a \wedge b$.
- Alice and Bob should not learn each other's secret bit (except what can be inferred: see note below).
- *Note:* Sometimes you can infer the other person's bit from the $a \wedge b$ output, and it's okay if the protocol leaks this information. For example, if Bob picks $b = 1$ and sees $a \wedge b = 0$, he can infer that $a = 0$. However, if Bob picks $b = 0$ and sees $a \wedge b = 0$, he cannot infer a (could be 0 or 1).

Protocol:

1. Alice generates four random symmetric keys: $K_{a=0}, \quad K_{a=1}, \quad K_{b=0}, \quad K_{b=1}$.
2. Alice uses the symmetric keys to compute four ciphertexts:

$$\mathsf{Enc}(K_{a=0},\ \mathsf{Enc}(K_{b=0}, 0))$$
$$\mathsf{Enc}(K_{a=0},\ \mathsf{Enc}(K_{b=1}, 0))$$
$$\mathsf{Enc}(K_{a=1},\ \mathsf{Enc}(K_{b=0}, 0))$$
$$\mathsf{Enc}(K_{a=1},\ \mathsf{Enc}(K_{b=1}, 1))$$

3. Alice sends all four ciphertexts to Bob.
4. Let K_a be $K_{a=0}$ or $K_{a=1}$, depending on which bit Alice chose. Alice sends K_a to Bob.
5. Let K_b be $K_{b=0}$ or $K_{b=1}$, depending on which bit Bob chose. Bob retrieves K_b from Alice.
6. For each of the four ciphertexts, Bob evaluates _____[Q3.5].

Three of the ciphertexts will decrypt to garbage. One of the ciphertexts will decrypt to either 0 or 1. The desired output $a \wedge b$ is the non-garbage value.

Q3.5 (1 point) Fill in the blank for step 6 above.

Your answer may include Enc, Dec, K_a, K_b, and C (one of the four ciphertexts Alice sends).

Q3.6 (1 point) In step 3, should Alice send the four ciphertexts in a random order?

- ◯ Yes, to prevent Bob from using the ciphertext order to always deduce Alice's bit a.
- ◯ Yes, to ensure each ciphertext uses a different encryption key.
- ◯ No, because Bob can already decrypt the non-garbage ciphertext.
- ◯ No, because encryption alone prevents Bob from always deducing Alice's bit a.

This content is protected and may not be shared, uploaded, or distributed.

Protocol (reprinted for your convenience):

1. Alice generates four random symmetric keys: $K_{a=0}$, $K_{a=1}$, $K_{b=0}$, $K_{b=1}$.
2. Alice uses the symmetric keys to compute four ciphertexts:

$$\mathsf{Enc}(K_{a=0},\ \mathsf{Enc}(K_{b=0}, 0))$$
$$\mathsf{Enc}(K_{a=0},\ \mathsf{Enc}(K_{b=1}, 0))$$
$$\mathsf{Enc}(K_{a=1},\ \mathsf{Enc}(K_{b=0}, 0))$$
$$\mathsf{Enc}(K_{a=1},\ \mathsf{Enc}(K_{b=1}, 1))$$

3. Alice sends all four ciphertexts to Bob.
4. Let K_a be $K_{a=0}$ or $K_{a=1}$, depending on which bit Alice chose. Alice sends K_a to Bob.
5. Let K_b be $K_{b=0}$ or $K_{b=1}$, depending on which bit Bob chose. Bob retrieves K_b from Alice.
6. For each of the four ciphertexts, Bob evaluates _____[Q3.5].

Three of the ciphertexts will decrypt to garbage. One of the ciphertexts will decrypt to either 0 or 1. The desired output $a \wedge b$ is the non-garbage value.

Q3.7 (1 point) Suppose that in Step 5, Bob retrieves K_b by telling Alice: "I want $K_{b=0}$" or "I want $K_{b=1}$". Why is this a bad idea?

- ◯ Because that would reveal Bob's bit b to Alice.
- ◯ Because Bob would not have the key required to decrypt the ciphertexts.
- ◯ Because $K_{b=0}$ and $K_{b=1}$ are both generated as a function of Bob's bit b.
- ◯ Because that would reveal Alice's bit a to Bob.

Q3.8 (2 points) Suppose that in Step 5, Bob retrieves K_b by asking for both keys. This is a bad idea because Bob can now reveal Alice's bit a.

Which expression, when evaluated on each ciphertext C, will reveal Alice's bit a?

Note: The version of this subpart that appeared on the exam erroneously flipped the order of decryption keys. This was clarified, and has been corrected for this version of the exam.

- ◯ $\mathsf{Dec}(K_b,\ \mathsf{Dec}(K_{a=0}, C))$
- ◯ $\mathsf{Dec}(K_b,\ \mathsf{Dec}(K_{a=1}, C))$
- ◯ $\mathsf{Dec}(K_{b=0},\ \mathsf{Dec}(K_a, C))$
- ◯ $\mathsf{Dec}(K_{b=1},\ \mathsf{Dec}(K_a, C))$

This content is protected and may not be shared, uploaded, or distributed.

Q3.9 (2 points) Suppose that in Step 5, Bob uses the *blind retrieval* protocol (from earlier in this question) to retrieve either $K_{b=0}$ or $K_{b=1}$ from Alice, without Alice knowing which one Bob chose to retrieve.

After the blind retrieval in step 5, which values are known to Bob? Select all that apply.

- ☐ K_a, the key $K_{a=0}$ or $K_{a=1}$ corresponding to the bit Alice chose.
- ☐ K_b, the key $K_{b=0}$ or $K_{b=1}$ corresponding to the bit Bob chose.
- ☐ The key $K_{a=0}$ or $K_{a=1}$ corresponding to the bit Alice did *not* choose.
- ☐ The key $K_{b=0}$ or $K_{b=1}$ corresponding to the bit Bob did *not* choose.
- ☐ Alice's bit a.
- ◯ None of the above

This content is protected and may not be shared, uploaded, or distributed.